




Shell & Tube Heat Exchangers

PRE-ENGINEERED SERIES: HCF

Standard **X**change
a xylem brand

HCF



MATERIALS

SHELL	Brass
TUBES	Copper with option for 90/10 or 70/30 CuNi Tube Diameter Options: 1/4", 3/8", and 5/8"
HUBS	Brass with optional SAE four bolts connections
BONNETS	Cast Iron with option for Cast Bronze
FEET & BOLTING	Carbon Steel

BCF/HCF/HFF STANDARD DESIGN CAPABILITIES

	DESIGN PRESSURE	DESIGN TEMPERATURE
Tube Side	150 psi 10.5 kg/cm ²	300°F 148.9°C
Shell Side	300 psi 21.1 kg/cm ²	300°F 148.9°C

DETAILS

- Compact design with shell diameters 2" to 8", standard tube lengths 8" to 72" with custom tube lengths to 144".
- Available in 1, 2 & 4 tube side pass configurations.
- Same day, three-day, or five-day Quick Ship Program available.
- ASME Code options available.

EXCHANGER TYPE:

Straight Tube
Fixed Tubesheet

ADVANTAGES:

Less costly than removable bundle exchangers.

Provides maximum heat transfer surface area per given shell and tube size.

Easily interchangeable with designs of various manufacturers.

Flanged lip baffles ensure close tolerance, high efficiency and additional tube support.

Enlarged bundle entrance area of hub/tubesheet design lowers entrance velocity and pressure loss.

Tube side can be steam or mechanically cleaned.

Only tube side fluids exposed to gaskets.

No packed joints.

LIMITATIONS:

No provision for differential expansion of tubes and shell.

Shell side may not be mechanically cleaned.